

PA Amplifier

CPA-5120

- ✓ 3 MIC Inputs, 2 AUX Inputs and 1 AUX Output for connection
- ✓ Speaker Output with Line Transformer 100V, 70V e 4/16 Ohm
- ✓ Muting Function
- ✓ Individual Volume Control
- ✓ Low and High Tone Control
- ✓ LED Level Meter for quick and easy monitoring of sound level
- ✓ Amplifier with Remote Out control and Phantom Power



Front View

Rear View

SPECIFICATIONS

- | | |
|--------------------------|---|
| ● Power Source | 110V AC / 220V AC, 50/60Hz |
| ● Power Consumption | 240W |
| ● Output | 120W |
| ● Max. Output Power | 180W |
| ● Frequency Response | 100Hz ~ 16KHz ±3dB |
| ● Distortion (THD) | <0.3% at 1000Hz, 1/3 Rated Output Power |
| ● Output | 4 ~ 6 ohm, 70V, 100V |
| ● AUX Output | 600 ohm, 250mV |
| ● Input | Mic 1,2,3 : 600 ohm, 6.0mV
Aux 1,2 : 10K ohm, 150mV (-17dB250) |
| ● S/N Ratio | Mic 1,2,3 : ≥66dB
Aux 1,2 : ≥70dB |
| ● Tone Control | Bass : ±10dB at 100Hz
Treble : ±10dB at 10,000Hz |
| ● Muting Function | 0 ~ -30dB |
| ● Unit Dimension (LxBxH) | 440 x 92 x 330 mm |
| ● Net Weight | 11.0 kg / 24.25 lbs |

All products information and specifications are subject to changes without prior notice.