

Portable P.A. Amplifier

CWR-1030

- 30 watts of power
- Able to connect multiple units for a larger audience group
- 1 Wired MIC input jack, 1 Wireless microphone and 1 AUX Input
- Come with SD and USB Media Player
- Voice Priority Switch
- ON/OFF Power switch to save power
- Built-in Lithium Rechargeable Battery





SPECIFICATIONS

Preliminary Datasheet

A) Wireless Receiver

Frequency Range 863 ~ 865MHz Frequency Stability ± 0.0005%

Sensitivity -97dB

Spurious Emission ≤ 45dB

Image and Spurious Rejection ≥ 40dB

AF Output SNR 80dB

1% Distortion

Power Source 8V

Current Consumption 120mA

Modulation Mode Channel Number

B) PA System

Output Power

Speaker

Distortion

AF Frequency Response

Input Signal

Output Signal

Recharging Time

Operating Time

Dimensions

Weight

650 MV

FM

1 CH

RMS 25W@ 4ohm, MAX 30W

6.5" Full Range Speaker

10%

100Hz ~ 15KHz (± 3dB)

1 X MIC In, 1 X AUX in

1 x LINE OUT

6 ~ 10 Hours

4 ~ 5 Hours

227 (L) x 206 (W) X 224 (H) mm

6.0 kg (includes battery)

All products information and specifications are subject to changes without prior notice.