

HDMI Matrix HM44



Front View

Rear View

comm HDMI Matrix **HM44** distributes 4 HDMI sources to any combination of 4 HDMI displays. Switch easily between sources and displays using remote control, front panel button or RS232 control.

- Supports up to 1080p
- Supports 48 bit deep full HD, Full 3D and 4K X 2K video
- Supports standard audio, DSD Audio and HD (HBR) Audio
- Supports ARC at output 1
- Supports 3D
- HDCP compliance
- Rack mountable

SPECIFICATIONS

- **Input** - HDMI female type A X 4
- **Output** - HDMI female type A X 4
3.5mm mini jack stereo audio female and SPDIF
- **Output Resolution** - 480i/480p/ 576i/ 720p/ 1080i / 1080p / 4k2k
- **Bandwidth** - 10.2Gps per channel
- **Frequency Range** - 25Mhz – 340MHz
- **Serial Port Control** - RS 232 9 pin female connector
- **Operating Temperature** - 0 to 45 degree Celsius
- **Power Adapter** - 12V DC3A
- **Dimensions** - 438 (L) x 170 (W) x 44 (H) mm
- **Net Weight** - 2.42 KG
- **Gross Weight** - 3.20 KG

All products information and specifications are subject to changes without prior notice.