

Integrated WizarSwitch IPC-6AUR

With Built-in USB Repeater

NEW!



comm Integrated WizarSwitch (IPC Series) - Designed to control your Audiovisual Equipment in the most simplified ways via RS-232 commands; reasonably priced and works with most projectors and plasma displays.

One Touch Selection with LED Back-Lit Indications on the selectors' buttons, you can easily control your displays with its various selector buttons (e.g. select the different input source, volume and/or screen controls etc)

Built-In Signal Amplifiers of 250MHz / 350MHz bandwidths to minimise signal-loss worries. Widely used in Classrooms, Auditoriums, Lecture Theatres, Conference Rooms etc.

FEATURES

Display Controller for your Projector, Plasma (Power ON/OFF, input source selections, volume control) via RS232 Commands

One Touch Selection with LED Back-Lit Indications

INPUTS : 2 VGA with USB, 1 Composite Video

OUTPUTS: 2 VGA, 2 USB, 1 Video (Composite)

Built-In Signal Amplifier of 250MHz

Digital Volume Control for sound level adjustments

Volume Control Knob for MIC Inputs sound adjustments

NEW Features!

- **STANDBY mode - MIC Volume Control usable**
- **PC1 with Audio: PC Monitor is usable even when Projector is OFF**
- **3 USB Connections with Built-in USB Repeater**

SELECTOR SWITCH

(with LED Back-Lit Indications)

- Display ON / OFF
- Blank (Toggle Button)
- Auto Sync (Toggle Button)
- Screen / Audio Volume (Toggle Button UP / DOWN)
- VGA with USB IN Selector (Switch between PC1 or PC2)
- HDMI / VIDEO / WIRELESS Selector
- Volume Control Knob (for MIC Inputs)

SPECIFICATIONS

A) Input

- PC1 / PC2 Signal - VGA (D-Sub 15-Pin Female)
- PC1 / PC2 Audio - 3.5mm Mini Jack
- Video Signal - Composite Video (RCA)
- Audio Signal - Stereo / Composite Audio (RCA)
- Microphone IN - 3.5mm Mini Jack
- USB 1 / USB 2 IN - USB Female Type B Connector
- USB IN - USB Female Type A Connector

B) Output

- PC Signal - VGA Bandwidth of 250MHz
- PC Signal - Monitor OUT, VGA Bandwidth 250MHz
- Video Signal
- Audio Signal
- Microphone OUT
- USB OUT

C) Communication Control

- Serial Control Port - RS232
- Baud Rate - 9600, 19200, 38400, 115200
- Data / Stop Bits - 8 Bits / 1 Bits
- No parity

D) Power

- DC 12V Power Adapter

All products information and specifications are subject to changes without prior notice.