

Touch Screen Control

WizPanel-1

- **✓** Compact Size
 - For table top or wall mounted design
- √ 18 Capacitive Touch Switches
 - Customization of the button controls
- ✓ Build-in processor
 - IR learner with RS232, RS485 and IR ports
- ✓ User-Friendly programming software

→ Applications: Home Automations, Classroom Controls,

Corporate Applications, Churches Automations,

Hotel Rooms and Conference Rooms etc



Buttons
 18 Capacitive Touch Switch LED indicators with backlight

Communication Ports 2 X RS-232, 2 X RS-485, 2 X IR port

RS-232 Even/ Odd. 9600, 19200, 38400 and stop bits

RS-485 Multidrop

IR Ports Build-In IR leaner and Transmitter

Control Mode

i) Toggle - LED will blink and codes will be transmitted
 ii) ON/OFF - LED will toggle between ON and OFF
 iii) Grouping - Only one button in the group will be lighted

iv) Marco - A sequence of commands will be transmitted with a delay of 2 seconds per button

Programming RS232

Power Supply
DC 12V (External)

Dimensions
 140 x 86 x 28.5 mm

Weight 160 gm

Package Includes - 12V DC Power Adapter x 1

- User Friendly Programming Software x 1

WizPanel-1 Diagram WizPanel 1 F1 F2 COMM

OPTIONAL ACCESSORIES

WP-MO1

Control interface for WizPanel to various Input/Output boards for automation process.

Specification: Input: 12VDC

Communication: Daisy Link RS232 (looping)

Selectable ID using Dip switch

Able to link up to 4 accessories board (4 sets of MO-1 for one WizPanel)

Options : LAN version Wireless version

Web base software for control

Intelligent control and monitoring via PC

WP-MR1

Relay I/O board for AC or DC control

Specification:

External and Internal Power Input: 12 VDC

All products information and specifications are subject to changes without prior notice.