Portable Wireless PA System

CWR-1150W

Wireless PA System, suitable for a wide range of events - indoors and outdoors

- Maximum power output of 150W
- One-touch wireless frequency synchronization
- Bluetooth MP3 player with USB/SD card support
- Built-in UHF 16 Frequency Receiver
- Voice priority function
- Power-saving ON/OFF switch
- Integrated battery level and charge indicator
- Built-in Rechargeable Lithium Battery



Front View



Rear View

Specifications

A) PA System	
Power Output	150W (max)
Speaker	8" Woofer Speaker, 1" Tweeter
Frequency Response	50Hz-18Khz ±3dB
Audio Input - Wired Mic	1 X MIC (1/4"XLR Combined)
Audio Input - Line-in	1 X Line In (3.5mm), 2 X RCA
Line Output	2 X RCA
Voice Priority	Yes
Power Supply AC	15V 4A/6A Power supply
Power Supply DC & Battery	11.1V 6A Lithium Battery
Recharging Time	8 ~ 10 Hours
Operating Time (depends on usage)	6 ~ 8 Hours
Battery Indicator	Integrated battery level and charge indicator (LED)
Dimensions	275 (L) x 265 (W) x 395 (H) mm
Weight	Approx 8.5 kg (includes battery)
Audio Player	Bluetooth MP3 player with USB/SD
B) Wireless Receiver	
Wireless Microphone - Option 1	**Model : CW5-H Handheld microphone x 2**
Wireless Microphone - Option 2	**Model : CW5-BC Lavalier mic with bodypack transmitter x 2**
Wireless Receiver Module	Dual Channel
Frequency Channel	UHF 16 Frequency
Oscillation Mode	PLL Synthesized
Frequency Range	UHF 640 to 680 MHz
Receiving Sensitivity	-95dB
Spurious Emission	< 55dB
SNR Rate	> 95dB
Indicator	LED RF Signal
Wireless Mic RF Output Power	10mW

Wireless microphone and wireless receiver

Choose from 2 options



Option 1 :
CW5-H
Handheld microphone x 2



Option 2 :
CW5-BC Lavalier mic with bodypack transmitter x 2

All products information and specifications are subject to changes without prior notice.